



Rack/Tower Design
Enables integration into a wide variety of environments.
Optional rack-mount rail available.

Advanced Digital Control Technology
Achieves higher reliability and greater immunity from Utility power problems to the connected load.

Wide Input Frequency and Voltage Windows
A wide input frequency window from 45Hz to 65Hz and a voltage input window of 60~144Vac for 120Vac for 120Vac system.

Unity Input Power Factor
Meets today's industry standard for energy saving and low current harmonic pollution to the Utility.

Double Conversion On-line Technology
Completely re-generates the Utility Power to correct power disturbances in the Mains. The unit provides clean AC power with VFI (Voltage and Frequency Independent) from the Utility.

User Friendly Display
An easy-to-read LCD/LED display provides real-time indication of all major system parameters and system status including load level, battery level, bad battery, site wiring fault, overload and programmable outlet for easy service.

Emergency Shutdown Control Through EPO
Allows users to shut down the UPS completely in an emergency to ensure a safe operating environment.

Powerful Built-in Charger
Provides approximately 0.3C charging ability to re-charge internal battery to 90% in 3 hours.

Specifications	Continuity 1K	Continuity 2K/3K
AC Input		
Voltage Window	80V-288Vac	
Current	2.9A Max.	
Frequency	50Hz/60Hz +/-10%	
DC Output		
Voltage(No Load)	41.0 +/-0.5Vdc	82.0 +/-0.5Vdc
Charging Current	4A	2A
Efficiency (Full Load)	>80%	
Output Capacity	Max. 160W	
Operation Mode	Constant Voltage with Current Limitation	
Mechanical		
Dimension	mm	88H x 206W x 69D
	inch	3.5H x 8.1W x2.7D
Net Weight	0.55kg (1.21lbs)	

Programmable Receptacles
Remote Reboot and Load Shedding via software reserving back-up power for critical loads.

Hot Swappable Battery
Allows battery replacement without UPS or critical load interruption.

The Communication Software
The bundled communication software allows the control of the UPS and graceful shutdown when Utility fails.

- Users Can:
- Remotely test the major operating functions of the UPS,
 - Communicate via SNMP/Web/Network adapter,
 - Access UPS functions via the Web,
 - Alert users via SMS messages against specific events.

Customer Options Slot
The Options Slot allows further flexibility in Network configuration. An internal 2nd RS232 card, 2nd USB card, SNMP card or Dry Contact card provide isolated contacts for industrial and remote alarm panel application.

Downloadable Setting Tool
Voltage Configuration, UPS Mode Selection, Output Voltage Fine Tuning, Bypass Voltage Window, Frequency Synchronized Window and Programmable Outlet Setting can be re-configured by the setting tool.

Extended Runtime Capability
Enables users to connect additional battery banks by simply plugging in the battery connectors between the UPS and battery banks without requiring additional chargers.

Optional External Bypass Switch
Ensures continuous supply of power to the critical load in the event of electronic failure, overload, over-temperature, or scheduled maintenance.

RS232 and USB Communication Interfaces
The advanced technology allows the RS232, USB and SNMP slot to be activated simultaneously.

Super Compact Convertible Design
With a most compact 2U design, the UPS occupies less space in a 19" rack cabinet, or in the 21" rack cabinet with the optional 21" Rack accessories. The convertible design enables integration into a wide variety of environments.

Power

Continuity 1000-3000

Convertible Indoor On-line UPS Series



- Feature rich on-line UPS Series with rack / tower convertible design with rotating LCD panel enabling easy integration into a wide variety of applications and locations
- Wide input power frequency and voltage window accommodates broad operating range for different working requirements
- Advanced digital control technology achieves higher reliability and greater immunity from utility power problems
- Emergency shutdown control through EPO complies with national safety regulations and local code
- Programmable receptacles enable flexible power backup
- Powerful built-in charger shortens battery charging time and extends runtime
- Hot swappable battery allows replacement without interruption to critical loads

The Continuity 1000-3000 Series, equipped with field-proven Digital Signal Processor, is the ideal UPS system for Servers, Networks, Storage, Telecommunications and Industrial Equipment.



Continuity 1000-3000 Series

Specifications				
Models	Continuity 1000		Continuity 2000	Continuity 3000
Input				
Voltage Window	60~144Vac for 120V system			
Frequency	50/60+/-5% (Auto Sensing)			
Phase/Wire	Single, Line + Neutral + Ground			
Power Factor	>0.99 (Full Load)			
Output				
Voltage	100/110/115/120/127Vac			
Voltage Regulation	<±0.1% until low battery warning			
Capacity	1000VA/800W	2000VA/1600W	3000/2400W	
Power Factor	0.8* Lagging			
Wave Form	Sine Wave, THD<3% (no load to full load)			
Frequency Stability	±0.1% unless synchronized to line			
Frequency Regulation	3Hz or 1Hz (Setting by software)			
Transfer Time	0 m sec			
Crest Factor	3:1			
Efficiency (AC to AC)	>85%		>88%	
Autonomy (Built-in Battery)	7.9 min		6.5min	
DC Start	Yes			
Battery				
Type	Sealed Lead Acid Maintenance Free			
Capacity	7Ah		9Ah	
Quantity	3	6		
Voltage	36Vdc	72Vdc		
Recharge Time	3 hours to 90%			
Built-in Charger (max. Charging Current)	1.8A	2.1A	2.7A	
Display				
LED	Normal, Battery, Bypass, Programmable Outlet 1, Programmable Outlet 2, Self-Test, Battery Weak & Bad, Site Wiring Fault , Fault, Overload, and Load/Battery Level conditions.			
Key	On button / Off button (Test / Alarm silence button)			
Self-Diagnostics	Upon Power On and Software Control			
Communication Slots	Relay contact board or SNMP card			
Protection				
Overload AC Mode & Backup Mode (delay before switching to bypass)	<105% continuously. >106%~120% for 30 seconds transfer to bypass >121%~150% for 10 seconds transfer to bypass >150% immediately transfer to bypass Buzzer continuously alarms			
Bypass Mode	<105% continuously. >106%~120% for 250 seconds shut down >121%~130% for 125 seconds shut down >131%~135% for 50 seconds shut down >136%~145% for 20 seconds shut down >146%~148% for 5 seconds shut down		>149%~157% for 2 seconds shut down >158%~176% for 1 seconds shut down >177%~187% for 0.32 seconds shut down >188% for 0.16 seconds shut down Buzzer continuously alarms	
Short Circuit	Hold Whole System			
Overheat	AC Mode: Switch to Bypass; Backup Mode: UPS shuts down immediately			
Battery Low	Alarm and Switch Off			
EPO	UPS shuts down immediately			
Battery	Advanced Battery Discharge Management (ABDM)			

Noise Suppression	115V System	400 Joules		
	230V System	300 Joules		
Models		Continuity 1000	Continuity 2000	Continuity 3000
Alarms				
Audible and Visual		Line Failure, Battery Low, Overload, System Fault Conditions		
Mechanical				
Dimensions	mm	440W x 88H x 405D	440W x 88H x 650D	
	inch	17.3W x 3.5H x 16D	17.3W x 3.5H x 25.6D	
Outlets 120Vac		6 x NEMA 5-15R	2x5-15R + 2 x 5-20R	4x5-15R + 1xL5-30R
Outlets 230Vac		6 x IEC320-C13		4 x IEC320-C13 1 x IEC320-C19
Net Weight		15.1kg (33.3lbs)	27.9kg (61.5lbs)	29.7kg (65.4lbs)
Environment				
Operating Temperature		0-40°C (32-104°F)		
Altitude		0~2000m/6600ft up to 40°C (104°F), 3000m/9900ft up to 35°C (95°F)		
Humidity		90% RH Maximum, Non-Condensing		
Noise		<50dB (at 1 meter/3.3ft)		
Computer Interface				
Interface Type		Standard RS232 and USB Interfaces		
Communication Slots		Relay contact board or SNMP card		
Agency Compliance				
Quality Assurance		ISO9001 Certified Company		
Safety Standard		EN62040-3 complied		
Performance		EN62040-3 complied		
EMC Standard		EN62040-2, EN61000-3-2, EN61000-3-3, FCC Class A		
Marks		CE, UL, cUL, FCC		

Battery Pack

Model		BP Continuity 1000	BP Continuity 2000	BP Continuity 3000
Battery Type		7Ah		9Ah
Maximum Quantity		12pcs		
Output Voltage		36Vdc	72Vdc	
Weight Without Batteries		8kg (17.7lbs)		
Weight With Batteries		38kg (83.7lbs)		
Dimensions	mm	88H x 440W x 650D		
	inch	3.5H x 17.3W x 25.6D		

*Based on load(%)- 0~33/33~66/66~100% respectively.
** Operation 0~3°C (54°F) if the power factor is at 0.8.
Specifications are subject to change without prior notice.