

Power

FXM 1100

Rugged UPS Module



FXM 1100

- 1100W/VA UPS module designed to operate in extreme environments and provide maximum flexibility while ensuring critical loads remain protected and running during power outages and other power disturbances
- Wide range Automatic Voltage Regulation (AVR) lengthens battery life by providing protection without transferring to backup mode during voltage surge or sag
- Independently programmable control and report dry contacts allow monitoring and controlling of key functions
- Temperature compensated battery charging protects batteries from overcharging or undercharging at extreme temperatures, extending the life of the battery
- Local and remote monitoring and control via RS232 port and Ethernet SNMP interface*
- UPS panels can be rotated, improving usability and viewing convenience

Alpha FXM is a line of rugged UPS power modules used worldwide in the most demanding environments where clean backup power is needed. Designed to perform in the most extreme demanding environments, Alpha FXM units ensure equipment in security, communications, traffic, industrial environments, and many other critical applications remains safe and protected from power disturbances. Thanks to its powerful programmable battery charger, the FXM is capable of providing the runtime you need. All FXM models are available in 120Vac and 230Vac.

*Ethernet SNMP card is standard on the 120Vac model and optional on the 230Vac model

FXM 1100 Rugged UPS Module

Consult your Alpha representative for P/N configurations

Electrical

>120Vac Model

Battery string voltage:.....48Vdc

Nominal voltage:.....120Vac

Frequency:.....60/50Hz ±5% (auto-detection)

Input:

Voltage range:.....85 to 175Vac

Current:.....9.8A nominal

Output:

Waveform:.....Pure sine wave

Nominal voltage:.....120Vac

Voltage regulation:.....+/- 10% over input voltage range

Power at 50°C:.....1100W/VA

Frequency:.....Output frequency = Input frequency

>230Vac Model

Battery string voltage:.....48Vdc

Nominal voltage:.....230Vac

Frequency:.....60/50Hz ±5% (auto-detection)

Input:

Current:.....5.1A nominal

Voltage range:.....150 to 328Vac

Output:

Waveform:.....Pure sine wave

Nominal voltage:.....230Vac

Voltage regulation:.....+/- 10% over input voltage range

Power:.....1100W/VA

Mechanical

Dimensions:

mm:.....133H x 394W x 222D

inches:.....5.22H x 15.5W x 8.75D

Weight:.....16kg (35lbs)

Environmental

Operating temp range*:.....-40 to 74°C (-40 to 165°F)

Audible noise @ 25°C:.....45dBA @ 1 meter (39in)

*Derates after 55°C

Performance








Typical output voltage THD:.....<3%

Typical efficiency:.....>98% (resistive load)



Typical transfer time:.....<5ms

Power Connector Options

120Vac Model

Input		Output	
Standard	 Terminal Block	 Terminal Block	
Optional	 Terminal Block	  Terminal Block + Dual 5-15R	
	 IEC**	 IEC**	

230Vac Model

Standard	 Terminal Block	 Terminal Block
----------	---	--

**FXM models with IEC connectors come with 4 lines LCD display instead of the traditional 2 lines display

Agency Compliance***

Electrical safety:.....UL1778, CSA 22.2 No 107.3-03

Marks:  

EMI:.....Class A FCC/CISPR
[EN 50091-2:1995]

***Compliance only applies to units with standard input and output connectors.

Contact us for compliance information on models with optional power connectors

****CE applies to 230Vac version only